



# Acoustical Surfaces, Inc.

SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION CONTROL SPECIALISTS

123 Columbia Court North • Suite 201 • Chaska, MN 55318

(952) 448-5300 • Fax (952) 448-2613 • (800) 448-0121

Email: [sales@acousticalsurfaces.com](mailto:sales@acousticalsurfaces.com)

Visit our Website: [www.acousticalsurfaces.com](http://www.acousticalsurfaces.com)

**We Identify and S.T.O.P. Your Noise Problem**



**ACOUSTIK™**  
acoustic subflooring

- **High Performance Noise Control**
- **Cost Effective**
- **Recycled Rubber Material**
- **Easy to Install and Work with**



**MATERIAL:** Recycled Rubber

**FEATURES:** Flat, semi-smooth

**APPLICATIONS:** Effective Sound Control


**ROLL SIZE:** 4' x 25' – Sold in full rolls

**THICKNESS:** 1/4", 3/8", 1/2"

**COLOR:** Black

**FLAMMABILITY:** ASTM E-84 Flame Spread: 83; Smoke Developed: 315

**INSTALLATION:** Adhesive Poly 300 or DA5



**COMPOSITION:**

Wood Floor

Adhesive


8-mm (5/16") Acoustik

Membrane

Adhesive

Concrete slab (8")

**FIIC 62**



**COMPOSITION:**

Wood Floor

Adhesive

8-mm (5/16") Acoustik Membrane

Adhesive

38-mm Concrete Slab

11.1-mm (7/16") Particleboard

38 x 235-mm (2" x 10") Floor Joist

RSI 1.470-mm (2-3/4") Sound Insulation

**FIIC 61**

The 25 year limited warranty is offered by Tuile Duro Inc. Acoustik is warranted against degradation of the physical properties of the products rubber material when installed in accordance with the manufacturers installation instructions. The limited warranty covers replacement of the Acoustik product only, labor, materials and other cost to repair and replace floor components are not warranted. No other warranty is either expressed or implied. All liability associated with the use of Acoustik is assumed by Tuile Duro Inc.